



# MODEL SPD

## Model SPD Steel Square Plaque Face Diffuser

Panel Size	Neck Size	Area Ak	Inlet Velocity	400	500	600	700	800	900	1000	1200
24x24	6"	.196  .077	CFM	80	100	120	135	155	175	195	235
			Ps	.003	.004	.006	.006	.008	.011	.014	.021
			Throw	4	6	7	8	8	9	9	10
			NC	<15	<15	<15	<15	15	18	21	26
24x24	8"	.349  .136	CFM	140	175	210	245	280	315	350	420
			Ps	.007	.012	.017	.023	.030	.038	.047	.067
			Throw	6	7	9	10	11	12	13	14
			NC	<15	<15	<15	17	21	25	28	34
24x24	10"	.545  .213	CFM	220	275	325	380	435	490	545	655
			Ps	.016	.025	.034	.047	.061	.078	.096	.139
			Throw	7	9	11	13	14	15	16	17
			NC	<15	<15	15	21	26	30	33	37
24x24	12"	.785  .307	CFM	315	395	470	55	63	725	785	940
			Ps	.027	.042	.059	.081	.107	.133	.165	.236
			Throw	9	11	13	15	17	18	19	21
			NC	<15	<15	17	22	27	30	33	38
24x24	14"	1.069  .418	CFM	430	535	640	750	855	960	1070	1285
			Ps	.031	.049	.069	.095	.124	.156	.194	.280
			Throw	10	13	15	18	20	21	22	24
			NC	<15	<15	20	25	30	33	36	40
24x24	15"	1.227  .479	CFM	490	615	735	860	980	1105	1225	1475
			Ps	.038	.060	.086	.117	.152	.194	.238	.345
			Throw	11	14	16	19	21	23	24	26
			NC	<15	<15	20	27	32	35	37	41

### Performance Notes

All Units have been tested in accordance with ANSI/ASHRAE 70-2006. Data in table is derived from such testing.

Ps - Static pressure required to obtain listed cfm, units of inches water gauge (in. wg.).

NC - Calculated noise criteria using 10 dB per octave room attenuation (dimensional).

Throw - Non-isothermal horizontal throw, in feet, for a terminal velocity of 50 fpm.

Ak - Area Factors

Inlet Velocity = fpm (Feet Per Minute)